LEGAL NOTICE NOTICE TO CONTRACTORS

Sealed proposals will be received at the Township Hall of Richfield Township; 3 986 Road J; Deshler OH 43516, Fiscal Officer Debra Shepard, or mailed to: 4 917 Road L McClure OH 43534, until Tuesday, May 31, 2022 at 8:00 P.M. for the improvement of the following Township roads (approximately 33.26 miles):

Bartlow Township

Road 5 from Road A to Road G

Damascus Township

Road 3 from Road M to Road N

Road O4 from Road 6A to Road 7

Road 6A from US 6 to Road N

Harrison Township

Road O3 from Road 10 to Road 11

Road N from Road 11 to Road 12

Road 12 from Road P to RoadP3

Road N from Road 8 to SR 109

Road P3 from Road 8 to SR 109

Campbell's Turn Lane (Road 12)

Liberty Township

Road U from Road 9 to Road 10

Pleasant Township

Road 14A from Road B to Road A

Road C from SR 108 to 12A (includes Marion Township)

Road C2 from SR 108 to Road 13

Road 16 from Road F to SR 18

Road 19 From SR 18 to Steinmaier Road

Riad 19 from Road Y to Road 17B

Richfield Township

Road K from SR 65 to Road 5 (3 feet each edge then entire road)

Road 1 from Road H to Road G

Road 5 from Road J to SR 281

Road H from Road 1 to Road 7- Fog Seal Only

Washington Township- Double Chip and Seal

Road 1D from Road S3 to Road T3

Road 5B from US 24 to Road T

Road S2 from Road 5B to Dead End

Road 6C from Road 424 to Road S

Road R2 from 6C to Dead End

Road 2 from Road V to New Pavement

Richfield Township, Henry County, Ohio, in accordance with estimates and specifications on file with the Richfield Township Fiscal Officer.

Bidding documents are available online at www.henrycountyengineer.com

Bids are to be submitted on a unit price basis.

The contracts will be awarded to the lowest, competent and responsible bidder.

Each bidder is required to file with his bid a bid guaranty in the form of either:

- 1. A bond for the full amount of the bid; or
- 2. A certified check, cashier's check or letter of credit pursuant to Chapter 1305 of the Ohio Revised Code, in

the amount of ten (10%) percent of the bid price as guarantee that, if the contract be awarded on such bid, the bidder will enter into a contract and the performance of it will be properly secured.

The successful bidder, if using a (10%) bid guaranty, shall be required to provide a contract performance and payment bond for the full amount of the bid.

Estimated cost of the improvements is:

\$644,650.00

Prevailing Wage Rates per Section 4115 of the Ohio Revised Code shall prevail on this project.

The Board of Trustees reserves the right to award separate contracts for the above noted improvements. The Board of Trustees reserves the right to reject any or all bids.

BY ORDER OF THE BOARD OF TRUSTEES RICHFIELD TOWNSHIP HENRY COUNTY, OHIO

Debra Shepard, Fiscal Officer 4 917 Road L McClure OH 43534

Board of Trustees To:

Bartlow Township

Henry County, Ohio

Road 5 from Road A to Road G Length: 31600 Feet or 5.98

Mile(s)

Width: 16 Feet on Average (Approx. 56440 S.Y. including radius and driveway

work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	22,580	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	565	C.Y.	Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	8,470	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Rid		¢

Total Bid

To: Board of Trustees

Damascus Township

Henry County, Ohio

Road 3 from Road M to Road N Length: 5280 Feet or 1 Mile(s)

Width: 14.5 Feet (Approx. 8555 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,425	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	90	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,285	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: **Board of Trustees**

> Damascus Township Henry County, Ohio

5.31.22

Road O4 from Road 6A to Road 7 Length: 2660 Feet or 0.5 Mile(s)

Width: 15 Feet (Approx. 4460 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	1,785	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	45	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	670	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

Total Bid

Board of Trustees To:

> Damascus Township Henry County, Ohio

5.31.22

Road 6A from US 6 to Raod N Length: 5285 Feet or 1 Mile(s)

Width: 15 Feet (Approx. 8840 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,540	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	90	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,330	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To:	Doord	of Trustees
10:	Board	of Trustees

Harrison Township

Henry County, Ohio

Road O3 b/ Road 10 and Road

11

Length: 5225 Feet or 0.99 Mile(s)

Width: 17.75 Feet (Approx. 10355 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,145	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	105	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,555	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: **Board of Trustees**

> Harrison Township Henry County, Ohio

5.31.22

Road N b/ Road 11 and Road 12 Length: 5165 Feet or 0.98 Mile(s)

Width: 17.75 Feet (Approx. 10230 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,095	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	105	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,535	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

Total Bid

To: **Board of Trustees**

> Harrison Township Henry County, Ohio

5.31.22

Road 12 b/ Road P and Road P3 Length: 2615 Feet or 0.5 Mile(s)

Width: 22.5 Feet (Approx. 6600 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	2,640	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	70	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	990	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

i otai bid

To: **Board of Trustees**

> Harrison Township Henry County, Ohio

5.31.22

Road N b/ Road 8 and SR 109 Length: 5255 Feet or 1 Mile(s)

Width: 17.75 Feet (Approx. 10435 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,175	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	105	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,570	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

Total Bid

To: **Board of Trustees**

> Harrison Township Henry County, Ohio

5.31.22

Road P3 b/ SR 109 and Road 8 Length: 5250 Feet or 0.99 Mile(s)

Width: 18 Feet (Approx. 10570 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,230	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	110	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,590	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Rid		\$

Total Bid

To: Board of Trustees

Harrison Township

Henry County, Ohio

Campbell's Turn Lane (Road 12) Length: 875 Feet or 0.17 Mile(s)

Width: 11.5 Feet (Approx. 1140 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	460	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	15	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	175	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To:	Board of Tru	istees
-----	--------------	--------

Liberty Township

Henry County, Ohio

Road U b/ Road 9 and Road 10 Length: 5265 Feet or 1 Mile(s)

Width: 16 Feet on Average (Approx. 56440 S.Y. including radius and driveway

work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,885	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	100	C.Y.	Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,460	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To:	Board of	Trustees

Pleasant Township

Henry County, Ohio

Road 14A b/ Road B and Road A Length: 5295 Feet or 1 Mile(s)

Width: 16 Feet (Approx. 9490 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,800	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	95	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Pleasant Township

Henry County, Ohio

Road C b/ SR 108 and Road 12A (also includes 1340 feet in Marion)

Length: 6615 Feet or 1.25 Mile(s)

Width: 14.5 Feet (Approx. 10720 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,290	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	110	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Pleasant Township

Henry County, Ohio

Road C2 b/ SR 108 and Road 13 Length: 5265 Feet or 1 Mile(s)

Width: 14.5 Feet (Approx. 8535 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,415	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	85	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Pleasant Township Henry County, Ohio 5.31.22

Road 16 b/ Road F and SR 18 Length: 5270 Feet or 1 Mile(s)

Width: 16.5 Feet (Approx. 9720 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,890	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	100	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Pleasant Township

Henry County, Ohio

Road 19 b/ SR 18 and Steinmaier Road

Length: 2610 Feet or 0.49 Mile(s)

Width: 15 Feet (Approx. 4390 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	1,760	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	45	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Pleasant Township

Henry County, Ohio

Road 19 b/ Road Y and Road

17B

Length: 7965 Feet or 1.51 Mile(s)

Width: 16 Feet (Approx. 14210 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	5,685	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	145	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	614	1	L.S.	Maintaining Traffic	\$	\$
4	624	1	L.S.	Mobilization	\$	\$
5	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Richfield Township

Henry County, Ohio

Road K b/ SR 65 and Road 5 Length: 5285 Feet or 1 Mile(s)

Width: 16 Feet (Approx. 9425 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal, Chip and Seal 3 feet each edge with 8's then chip seal entire road with 9's

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,770	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	95	C.Y.	Seal Coat, aggregate No. 9 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,415	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond Seal coat, bituminous material (MWS 90 or HFRS-	\$	\$
7	409	1,410	Gal	2) applied at 0.4 gallons per square yard 3 feet on each side Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard 3 feet on	\$	\$
8	409	35	C.Y.	each edge	\$	\$
				Total Bid		\$

To: **Board of Trustees**

> Richfield Township Henry County, Ohio

5.31.22

Road 1 b/ Road H and Road G Length: 5240 Feet or 0.99 Mile(s)

Width: 18 Feet (Approx. 10505 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	4,205	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	105	C.Y.	Seal Coat, aggregate No. 9 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,580	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

Total Bid

To: Board of Trustees

Richfield Township

Henry County, Ohio

Road 5 b/ Road J and SR 281 Length: 5270 Feet or 1 Mile(s)

Width: 16 Feet (Approx. 9415 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	3,770	Gal	Seal coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	95	C.Y.	Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	Spec.	1,415	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
4	614	1	L.S.	Maintaining Traffic	\$	\$
5	624	1	L.S.	Mobilization	\$	\$
6	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Richfield Township Henry County, Ohio 5.31.22

Road H b/ Road 1 and Road 7 Length: 31680 Feet or 6 Mile(s)

Width: 16 Feet (Approx. 56320 S.Y. including radius and driveway work)

Type: Fog Seal Only

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	Spec.	8,450	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
2	614	1	L.S.	Maintaining Traffic	\$	\$
3	624	1	L.S.	Mobilization	\$	\$
4	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

Board of Trustees To:

Washington Township

Henry County, Ohio

5.31.22

Road 1D from Road S3 to Road

Length: 5305 Feet or 1 Mile(s)

Width: 12.5 Feet (Approx. 7485 S.Y. including radius and driveway work)
Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	2,620	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	75	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	2,995	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	75	C.Y.		\$	\$
5	Spec.	1,125	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Washington Township Henry County, Ohio

Road 5B from US 24 to Road T Length: 4025 Feet or 0.76 Mile(s)

Width: 12 Feet (Approx. 5440 S.Y. including radius and driveway work)

Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	Description	<u>Unit Price</u>	<u>Total Price</u>
1	409	1,905	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	55	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	2,180	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	55	C.Y.	Second Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-	\$	\$
5	Spec.	820	Gal	0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: **Board of Trustees**

> Washington Township Henry County, Ohio

5.31.22

Road S2 from Road 5B to Dead

End

Length: 1290 Feet or 0.24 Mile(s)

Width: 10 Feet (Approx. 1455 S.Y. including radius and driveway work)

Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	510	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	15	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	585	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	15	C.Y.		\$	\$
5	Spec.	220	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

i otai Bid

To: **Board of Trustees**

> Washington Township Henry County, Ohio

5.31.22

Road 6C from Road 424 to Road

Length: 4865 Feet or 0.92 Mile(s)

Width: 11 Feet (Approx. 6015 S.Y. including radius and driveway work)

Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	2,105	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	60	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	2,410	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	60	C.Y.		\$	\$
5	Spec.	905	Gal	Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Washington Township Henry County, Ohio

Road R2 from 6C to Dead End Length: 1250 Feet or 0.24 Mile(s)

Width: 10.5 Feet (Approx. 1505 S.Y. including radius and driveway work)

Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	530	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	15	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	605	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	15	C.Y.	Second Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-	\$	\$
5	Spec.	230	Gal	0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

To: Board of Trustees

Washington Township Henry County, Ohio 5.31.22

Road 2 from Road V to Newer Pavement

Length: 3965 Feet or 0.75 Mile(s)

Width: 13.5 Feet (Approx. 5990 S.Y. including radius and driveway work)

Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

<u>Ref. #</u>	<u>Item</u>	Quantity	<u>Unit</u>	<u>Description</u>	<u>Unit Price</u>	<u>Total Price</u>
1	409	2,100	Gal	First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
2	409	60	C.Y.	First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard	\$	\$
3	409	2,395	Gal	Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard	\$	\$
4	409	60	C.Y.	Second Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-	\$	\$
5	Spec.	900	Gal	0.15 gal per square yard	\$	\$
6	614	1	L.S.	Maintaining Traffic	\$	\$
7	624	1	L.S.	Mobilization	\$	\$
8	103.05	1	L.S.	Contract Performance & Payment Bond	\$	\$
				Total Bid		\$

TOTAL ENTIRE BID \$_____

Date of Sale: May 31, 2022 at 8:00 P.M.

Chipseal of Various Roads

All work and material contracted for seal coating shall meet the requirements of the 1997 State of Ohio, Department of Transportation, Construction and Material Specifications. All other work shall meet the requirements of the State of Ohio, Department of Transportation, Construction and Material Specifications in effect on the date of sale, together with any modifications to the same stated herein. **This includes removing grass and other debris from the road surface.**

Fog seal (if applicable) shall be applied no less than 7 days after chip seal work is performed.

Spreading and placement of asphalt shall be done with full width paving equipment.

"Formed" or "Butt Type" construction joints shall be constructed at all pavement termini unless otherwise directed by the Township Trustees.

The asphalt binder grade for all asphalt concrete specified shall be PG 64-22.

Aggregate used in the asphalt concrete mix and for seal coating shall be State approved quarry run mineral aggregate.

Cut back asphalt may be used on applicable bid items between the period of October 15th and April 15th.

There are no restricted construction dates for the use of cut backs for penetration prime coat, maintenance mix or dust control.

Prevailing Wage Rates per Section 4115 of the Ohio Revised Code shall prevail on this project. A copy of the applicable wage rates may be obtained from the State of Ohio Wage and Hour Division via the internet at the following web site:

http://www.com.ohio.gov/laws

Should the bidder not have access to the internet, a complete set of the applicable wage rates are available at the office of the Henry County Engineer. A copy will be provided if requested.

Contractors are required to furnish the Township with a certificate of insurance in the minimum amount of \$1,000,000.00 primary and \$1,000,000.00 umbrella coverage. The Township, its elected office and employees shall be named as additional insured with respect to all activities under any agreement resulting from this bidding. The certificate of insurance shall provide that such insurance shall not be cancelled without thirty (30) days prior written notice to the Township. Contractors will replace certificate for any insurance expiring prior to the effective end date under any agreement resulting from this bidding.

Contractors shall maintain Worker's Compensation coverage as required by Ohio law. A copy of a valid Worker's Compensation certificate shall be submitted with the bid.

The Contractor shall indemnify and hold harmless the Township, its agents and employees from any and all losses, claims, damages, lawsuits, costs, judgments, expenses or any other liabilities which they may incur as a result of bodily injury, sickness, disease or death, or injury to or destruction of tangible property including the loss of use resulting therefrom, caused in whole or part by the negligent act or omission of the Contractor or any person directly or indirectly employed by any of them or any person for whose act any of them may be liable.

Accompanying this proposal is a bid guaranty in the form of either:

- 1) A bond for the full amount of the bid, on the above improvement; or
- 2) A certified check, cashier's check or letter of credit pursuant to Chapter 1305 of the Ohio Revised Code, in the

amount of ten percent (10%) of the bid on the above improvements, payable to the order of the Board of Trustees, RICHFIELD TOWNSHIP, which check or bond is to be forfeited if, in case this proposal is accepted, the undersigned shall fail to execute a contract within ten (10) days of Notice of Award.

This contract shall be under the direct supervision of the Applicable Township Trustees and the Henry County Engineer.

All items are approximate, and final measurement of completed items will govern final payment.

In the event of discrepancy between the unit and total price bid, the unit price shall prevail. The unit prices shall remain in effect and held firm for the term of this contract. ODOT Item 401.20 Asphalt Binder price adjustment does not apply.

The Contractor shall be responsible for all construction one (1) year after project completion and acceptance. The Contractor shall make all corrections as necessary by reason of noted defects. The Trustees will give notice of observed defects with reasonable promptness. In the event that the Contractor fails to make repairs, adjustments or complete other work which may be required by such defects, the Trustees may do so and charge the Contractor the costs incurred.

The Board of Trustees reserve the right to award separate contracts on the various roads described. The Board of Trustees further reserves the right to reject any or all bids.

The seal coating shall be completed on or before September 15, 2022.

For each calendar day that any work shall remain uncompleted after the stated completion date the appropriate sum, in accordance with the schedule of liquidated damages per Section 108.07 of the Standard Specifications of the State of Ohio Department of Transportation, will be deducted from any monies due the Contractor, not as a penalty but as liquidated damages; provided however, that due account shall be taken of any adjustment of the completion date granted by the Board of Trustees of Richfield Township.

A work day will be counted as lost if the Contractor's efficiency is reduced more than fifty (50%) percent on the critical items under construction at that time. Weekends and holidays will not be counted as lost work days.

Submitte	ea By:	
	CONTRACTOR	
Address:		
_		
Signed B	y:	
. 0	Name/Title	
	Phone Number	
	Email Address	
	Fax Number	