#### LEGAL NOTICE NOTICE TO CONTRACTORS

Sealed proposals will be received at the Township Hall of Richfield Township; 3 986 Road J; Deshler OH 43516, Fiscal Officer Debra Shepard, or mailed to: 4 917 Road L McClure OH 43534, until Monday, June 26th, 2023 at 8:00 P.M. for the improvement of the following Township roads (approximately 20.76 miles):

| Bartlow Township  |  |
|---|--|
| Road F2 from 6 and 7  |  |
| Road A from SR 65 and 2   |  |
| Road C from SR 65 and 5   |  |
| Road 3 from SR 18 and E   |  |
| Road 2A from E to Deshler Corporation                                     |  |
| Damascus Township   |  |
| Road M4 from 6 and 7  |  |
| Road 3A from P and Q  |  |
| Road 3A from M and N  |  |
| Pleasant Township   |  |
| Road 19 from Y and 17B  |  |
| Road A from 17A and 17  |  |
| Road A from SR 108 and 13   |  |
| Road 16A from Y and B   |  |
| Richfield Township  |  |
| Road J from 1 and 3   |  |
| Road 3 from L and M   |  |
| Washington Township- Double Chip and Seal                                 |  |
| Road 2B from S3 and US24 (include turnaround)                             |  |
| Road 2B from CR 424 and US 24 (include turnaround and both intersections) |  |
| Road 5B from U and T  |  |
| Road T2 from 3 and 4  |  |
| Road V3 from 6 and 7  |  |

Richfield Township, Henry County, Ohio, in accordance with estimates and specifications on file with the Richfield Township Fiscal Officer.

Bidding documents are available online at <u>www.henrycountyengineer.com</u>

Bids are to be submitted on a unit price basis.

The contracts will be awarded to the lowest, competent and responsible bidder.

Each bidder is required to file with his bid a bid guaranty in the form of either:

- 1. A bond for the full amount of the bid; or
- 2. A certified check, cashier's check or letter of credit pursuant to Chapter 1305 of the Ohio Revised Code, in the amount of ten (10%) percent of the bid price as guarantee that, if the contract be awarded on such bid, the bidder will enter into a contract and the performance of it will be properly secured.

The successful bidder, if using a (10%) bid guaranty, shall be required to provide a contract performance and payment bond for the full amount of the bid.

Estimated cost of the improvements is: \$472,445.00

Prevailing Wage Rates per Section 4115 of the Ohio Revised Code shall prevail on this project.

The Board of Trustees reserves the right to award separate contracts for the above noted improvements. The Board of Trustees reserves the right to reject any or all bids.

BY ORDER OF THE BOARD OF TRUSTEES RICHFIELD TOWNSHIP HENRY COUNTY, OHIO

Debra Shepard, Fiscal Officer 4 917 Road L McClure OH 43534

To: Board of Trustees

Township Road

Improvements

Henry County, Ohio

Bartlow- F2 between 6 and 7

Length: 5260 Feet or 1 Mile(s)

Width: 11 Feet (Approx. 6495 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

|               |        |                 |             | Total Bid  |                   | \$                 |
|---------------|--------|-----------------|-------------|--|-------------------|--------------------|
| 6             | 103.05 | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
| 5             | 624    | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 4             | 614    | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 3             | Spec.  | 975             | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 2             | 409    | 65              | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 1             | 409    | 2,600           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| <u>Ref. #</u> | Item   | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Bartlow- Road A between SR 65 and Road 2 Length: 10550 Feet or 2 Mile(s) Width: 15.5 Feet (Approx. 18220 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 7,290           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 185             | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 3             | Spec.       | 2,735           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Bartlow- Road C between SR 65 and 5 Length: 5245 Feet or 0.99 Mile(s) Width: 15.5 Feet (Approx. 9095 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 3,640           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 95              | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 3             | Spec.       | 1,365           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Bartlow- Road 3 between SR 18 and E Length: 5250 Feet or 0.99 Mile(s) Width: 18 Feet (Approx. 10540 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 4,220           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 105             | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 3             | Spec.       | 1,585           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Bartlow- Road 2A between E and Deshler Corp. Length: 2640 Feet or 0.5 Mile(s) Width: 14 Feet (Approx. 4130 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | Total Price |
|---------------|-------------|-----------------|-------------|--|-------------------|-------------|
| 1             | 409         | 1,655           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$          |
| 2             | 409         | 45              | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$          |
| 3             | Spec.       | 620             | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$          |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$          |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$          |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$          |
|               |             |                 |             | Total Bid  |                   | \$          |

TOTAL ENTIRE BID \$\_\_\_\_\_

To: Board of Trustees

Township Road

Improvements

Henry County, Ohio

Damascus- Road M4 between 6 and 7 Length: 5390 Feet or 1.02 Mile(s) Width: 15 Feet (Approx. 9055 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 3,625           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 95              | C.Y.        | Seal Coat, aggregate No. 9 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 1,360           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Damascus- Raod 3A between P and Q Length: 5730 Feet or 1.09 Mile(s) Width: 16 Feet (Approx. 10250 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | Total Price |
|---------------|-------------|-----------------|-------------|--|-------------------|-------------|
| 1             | 409         | 4,105           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$          |
| 2             | 409         | 105             | C.Y.        | Seal Coat, aggregate No. 9 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$          |
| 3             | Spec.       | 1,540           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$          |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$          |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$          |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$          |
|               |             |                 |             | Total Bid  |                   | \$          |

To: Board of Trustees Township Road Improvements Henry County, Ohio

Damascus- Road 3A between M and N

Length: 5300 Feet or 1 Mile(s)

Width: 13 Feet (Approx. 7715 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 3,090           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 80              | C.Y.        | Seal Coat, aggregate No. 9 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 1,160           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees

Township Improvement Project Henry County, Ohio

Pleasant- Road 19 between Y and 17B Length: 7960 Feet or 1.51 Mile(s) Width: 17 Feet (Approx. 15090 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 6,035           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 155             | C.Y.        | Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 2,265           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Improvement Project Henry County, Ohio

Pleasant- Road A between 17A and 17 Length: 4005 Feet or 0.76 Mile(s) Width: 16 Feet (Approx. 7170 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 2,870           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 75              | C.Y.        | Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 1,080           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Improvement Project Henry County, Ohio

Pleasant- Road A between SR 108 and 13 Length: 5250 Feet or 0.99 Mile(s) Width: 16 Feet (Approx. 9400 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 3,765           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 95              | C.Y.        | Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 1,415           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Improvement Project Henry County, Ohio

Pleasant- Road 16A between Y and B

Length: 9435 Feet or 1.79 Mile(s)

Width: 16 Feet (Approx. 16835 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 6,735           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 170             | C.Y.        | Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard         | \$                | \$                 |
| 3             | Spec.       | 2,525           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees

Township Improvement Project Henry County, Ohio

Richfield- Road J between 1 and 3 Length: 10595 Feet or 2.01 Mile(s) Width: 18 Feet (Approx. 21340 S.Y. including radius and driveway work) Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 8,540           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 215             | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 3             | Spec.       | 3,205           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees Township Improvement Project

Henry County, Ohio

Richfield- Road 3 between L and M

Length: 5350 Feet or 1.01 Mile(s)

Width: 15 Feet (Approx. 8960 S.Y. including radius and driveway work)

Type: Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description  | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|--|-------------------|--------------------|
| 1             | 409         | 3,585           | Gal         | Seal coat, bituminous material (MWS 90 or HFRS-<br>2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 2             | 409         | 90              | C.Y.        | Seal Coat, aggregate No. 89 (washed), applied and compacted at 24 lbs per square yard        | \$                | \$                 |
| 3             | Spec.       | 1,345           | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-<br>0.15 gal per square yard                   | \$                | \$                 |
| 4             | 614         | 1               | L.S.        | Maintaining Traffic  | \$                | \$                 |
| 5             | 624         | 1               | L.S.        | Mobilization   | \$                | \$                 |
| 6             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond  | \$                | \$                 |
|               |             |                 |             | Total Bid  |                   | \$                 |

To: Board of Trustees

Township Improvement Project Henry County, Ohio

Washington- Road 2B between S3 and US 24 (include turnaround) Length: 1570 Feet or 0.3 Mile(s) Width: 11 Feet (Approx. 1945 S.Y. including radius and driveway work) Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description   | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|---|-------------------|--------------------|
| 1             | 409         | 685             | Gal         | First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.35 gallons per square yard | \$                | \$                 |
| 2             | 409         | 20              | C.Y.        | First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard      | \$                | \$                 |
| 3             | 409         | 780             | Gal         | Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard | \$                | \$                 |
| 4             | 409         | 20              | C.Y.        | Second Seal Coat, aggregate No. 89 (washed),<br>applied and compacted at 24 lbs per square yard | \$                | \$                 |
| 5             | Spec.       | 295             | Gal         | Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 gal per square yard                          | \$                | \$                 |
| 6             | 614         | 1               | L.S.        | Maintaining Traffic   | \$                | \$                 |
| 7             | 624         | 1               | L.S.        | Mobilization  | \$                | \$                 |
| 8             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond   | \$                | \$                 |
|               |             |                 |             | Total Bid   |                   | \$                 |

To: Board of Trustees Township Improvement

Project Henry County, Ohio

Washington- Road 2B between CR 424 and US 24 (include turn around and both intersections) Length: 4310 Feet or 0.82 Mile(s) Width: 12 Feet (Approx. 5795 S.Y. including radius and driveway work) Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description   | <u>Unit Price</u> | Total Price |
|---------------|-------------|-----------------|-------------|---|-------------------|-------------|
| 1             | 409         | 2,030           | Gal         | First Seal Coat, bituminous material (MWS 90 or<br>HFRS-2) applied at 0.35 gallons per square yard  | \$                | \$          |
| 2             | 409         | 60              | C.Y.        | First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard  | \$                | \$          |
| 3             | 409         | 2,320           | Gal         | Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard   | \$                | \$          |
| 4             | 409         | 60              | C.Y.        | Second Seal Coat, aggregate No. 89 (washed),<br>applied and compacted at 24 lbs per square yard<br>Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 | \$                | \$          |
| 5             | Spec.       | 870             | Gal         | gal per square yard   | \$                | \$          |
| 6             | 614         | 1               | L.S.        | Maintaining Traffic   | \$                | \$          |
| 7             | 624         | 1               | L.S.        | Mobilization  | \$                | \$          |
| 8             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond   | \$                | \$          |
|               |             |                 |             | Total Bid   |                   | \$          |

To: Board of Trustees Township Improvement Project Henry County, Ohio

Washington- Road 5B between U and T Length: 5305 Feet or 1 Mile(s) Width: 11 Feet (Approx. 6555 S.Y. including radius and driveway work) Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description   | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|---|-------------------|--------------------|
| 1             | 409         | 2,295           | Gal         | First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.35 gallons per square yard   | \$                | \$                 |
| 2             | 409         | 70              | C.Y.        | First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard  | \$                | \$                 |
| 3             | 409         | 2,625           | Gal         | Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard   | \$                | \$                 |
| 4             | 409         | 70              | C.Y.        | Second Seal Coat, aggregate No. 89 (washed),<br>applied and compacted at 24 lbs per square yard<br>Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 | \$                | \$                 |
| 5             | Spec.       | 985             | Gal         | gal per square yard   | \$                | \$                 |
| 6             | 614         | 1               | L.S.        | Maintaining Traffic   | \$                | \$                 |
| 7             | 624         | 1               | L.S.        | Mobilization  | \$                | \$                 |
| 8             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond   | \$                | \$                 |
|               |             |                 |             | Total Bid   |                   | \$                 |

To: Board of Trustees Township Improvement Project Henry County, Ohio

Washington- Road T2 between 3 and 4 Length: 5275 Feet or 1 Mile(s) Width: 12.5 Feet (Approx. 7390 S.Y. including radius and driveway work) Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description   | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|---|-------------------|--------------------|
| 1             | 409         | 2,590           | Gal         | First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.35 gallons per square yard   | \$                | \$                 |
| 2             | 409         | 75              | C.Y.        | First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard  | \$                | \$                 |
| 3             | 409         | 2,960           | Gal         | Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard   | \$                | \$                 |
| 4             | 409         | 75              | C.Y.        | Second Seal Coat, aggregate No. 89 (washed),<br>applied and compacted at 24 lbs per square yard<br>Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 | \$                | \$                 |
| 5             | Spec.       | 1,110           | Gal         | gal per square yard   | \$                | \$                 |
| 6             | 614         | 1               | L.S.        | Maintaining Traffic   | \$                | \$                 |
| 7             | 624         | 1               | L.S.        | Mobilization  | \$                | \$                 |
| 8             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond   | \$                | \$                 |
|               |             |                 |             | Total Bid   |                   | \$                 |

To: Board of Trustees Township Improvement Project

Henry County, Ohio

Washington- Road V3 between 6 and 7 Length: 5200 Feet or 0.98 Mile(s) Width: 12.5 Feet (Approx. 7295 S.Y. including radius and driveway work) Type: Double Chip Seal, 1997 ODOT Spec 409 W/ Fog Seal

| <u>Ref. #</u> | <u>Item</u> | <u>Quantity</u> | <u>Unit</u> | Description   | <u>Unit Price</u> | <u>Total Price</u> |
|---------------|-------------|-----------------|-------------|---|-------------------|--------------------|
| 1             | 409         | 2,555           | Gal         | First Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.35 gallons per square yard   | \$                | \$                 |
| 2             | 409         | 75              | C.Y.        | First Seal Coat, aggregate No. 8 (washed), applied and compacted at 24 lbs per square yard  | \$                | \$                 |
| 3             | 409         | 2,920           | Gal         | Second Seal Coat, bituminous material (MWS 90 or HFRS-2) applied at 0.4 gallons per square yard   | \$                | \$                 |
| 4             | 409         | 75              | C.Y.        | Second Seal Coat, aggregate No. 89 (washed),<br>applied and compacted at 24 lbs per square yard<br>Fog Seal, SS-1H Dilute 50/50, Applied at 0.10-0.15 | \$                | \$                 |
| 5             | Spec.       | 1,095           | Gal         | gal per square yard   | \$                | \$                 |
| 6             | 614         | 1               | L.S.        | Maintaining Traffic   | \$                | \$                 |
| 7             | 624         | 1               | L.S.        | Mobilization  | \$                | \$                 |
| 8             | 103.05      | 1               | L.S.        | Contract Performance & Payment Bond   | \$                | \$                 |
|               |             |                 |             | Total Bid   |                   | \$                 |

6.26.23

TOTAL ENTIRE BID \$\_\_\_\_\_

Date of Sale: June 26, 2023 at 8:00 P.M.

#### **Chipseal of Various Roads**

All work and material contracted for seal coating shall meet the requirements of the 1997 State of Ohio, Department of Transportation, Construction and Material Specifications. All other work shall meet the requirements of the State of Ohio, Department of Transportation, Construction and Material Specifications in effect on the date of sale, together with any modifications to the same stated herein. **This includes removing grass and other debris from the road surface.** 

#### Fog seal (if applicable) shall be applied no less than 7 days after chip seal work is performed.

Spreading and placement of asphalt shall be done with full width paving equipment.

"Formed" or "Butt Type" construction joints shall be constructed at all pavement termini unless otherwise directed by the Township Trustees.

The asphalt binder grade for all asphalt concrete specified shall be PG 64-22.

Aggregate used in the asphalt concrete mix and for seal coating shall be State approved quarry run mineral aggregate.

Cut back asphalt may be used on applicable bid items between the period of October 15<sup>th</sup> and April 15<sup>th</sup>.

There are no restricted construction dates for the use of cut backs for penetration prime coat, maintenance mix or dust control.

Prevailing Wage Rates per Section 4115 of the Ohio Revised Code shall prevail on this project. A copy of the applicable wage rates may be obtained from the State of Ohio Wage and Hour Division via the internet at the following web site: <u>http://www.com.ohio.gov/laws</u>

Should the bidder not have access to the internet, a complete set of the applicable wage rates are available at the office of the Henry County Engineer. A copy will be provided if requested.

Contractors are required to furnish the Township with a certificate of insurance in the minimum amount of \$1,000,000.00 primary and \$1,000,000.00 umbrella coverage. The Township, its elected office and employees shall be named as additional insured with respect to all activities under any agreement resulting from this bidding. The certificate of insurance shall provide that such insurance shall not be cancelled without thirty (30) days prior written notice to the Township. Contractors will replace certificate for any insurance expiring prior to the effective end date under any agreement resulting from this bidding.

Contractors shall maintain Worker's Compensation coverage as required by Ohio law. A copy of a valid Worker's Compensation certificate shall be submitted with the bid.

The Contractor shall indemnify and hold harmless the Township, its agents and employees from any and all losses, claims, damages, lawsuits, costs, judgments, expenses or any other liabilities which they may incur as a result of bodily injury, sickness, disease or death, or injury to or destruction of tangible property including the loss of use resulting therefrom, caused in whole or part by the negligent act or omission of the Contractor or any person directly or indirectly employed by any of them or any person for whose act any of them may be liable.

Accompanying this proposal is a bid guaranty in the form of either:

1) A bond for the full amount of the bid, on the above improvement; or

2) A certified check, cashier's check or letter of credit pursuant to Chapter 1305 of the Ohio Revised Code, in the

amount of ten percent (10%) of the bid on the above improvements, payable to the order of the Board of Trustees, RICHFIELD TOWNSHIP, which check or bond is to be forfeited if, in case this proposal is accepted, the undersigned shall fail to execute a contract within ten (10) days of Notice of Award.

This contract shall be under the direct supervision of the Applicable Township Trustees and the Henry County Engineer.

All items are approximate, and final measurement of completed items will govern final payment.

In the event of discrepancy between the unit and total price bid, the unit price shall prevail. The unit prices shall remain in effect and held firm for the term of this contract. ODOT Item 401.20 Asphalt Binder price adjustment does not apply.

The Contractor shall be responsible for all construction one (1) year after project completion and acceptance. The Contractor shall make all corrections as necessary by reason of noted defects. The Trustees will give notice of observed defects with reasonable promptness. In the event that the Contractor fails to make repairs, adjustments or complete other work which may be required by such defects, the Trustees may do so and charge the Contractor the costs incurred.

The Board of Trustees reserve the right to award separate contracts on the various roads described. The Board of Trustees further reserves the right to reject any or all bids.

The seal coating shall be completed on or before September 15, 2023.

For each calendar day that any work shall remain uncompleted after the stated completion date the appropriate sum, in accordance with the schedule of liquidated damages per Section 108.07 of the Standard Specifications of the State of Ohio Department of Transportation, will be deducted from any monies due the Contractor, not as a penalty but as liquidated damages; provided however, that due account shall be taken of any adjustment of the completion date granted by the Board of Trustees of Richfield Township.

A work day will be counted as lost if the Contractor's efficiency is reduced more than fifty (50%) percent on the critical items under construction at that time. Weekends and holidays will not be counted as lost work days.

Submitted By:\_\_\_\_\_CONTRACTOR
Address:\_\_\_\_\_
Signed By:\_\_\_\_\_
Name/Title
Phone Number

Email Address

Fax Number