

HENRY COUNTY

ROAD 'Y'

(DEF – HEN CO. LINE TO C.R. 13)

PLEASANT TWP.

CENTER LINE CONTROL
&
WITNESSES

2005

Witness Ties for Road Y

Station	Point Description	Witness Ties - Updated 11/29/05
0+00.00	RR Spike	64.89' NNE to duplex E/side power pole 51.13' E to duplex N/side power pole 28.34' SW to duplex SE/side cable marker
3+82.07	RR Spike	23.63' NNE to duplex W/side power pole 31.60' S to duplex W/side power pole 22.44' SW to "+" NW corner catch basin
21+14.01	RR Spike	20.52' W to duplex E/side power pole 47.02' NW to duplex in power pole 89.63' SE to near anchor bolt NW/side grain bin
28+07.99	RR Spike	17.40' N to duplex W/side power pole 13.25' SSE to 5/8" iron pin at edge of pavement 12.08' WSW to 5/8" iron pin at edge of pavement
33+48.83	RR Spike	17.74' SE to 5/8" iron pin at edge of pavement 17.05' SW to 5/8" iron pin at edge of pavement
42+34.02	RR Spike	22.85' SW to duplex (new) W/side of cable marker 7.47' NNE to 5/8" iron pin at edge of pavement 18.10' SSE to 5/8" iron pin at edge of pavement
57+55.23	RR Spike	66.52' SE to duplex (new) SW/side of cable marker 30.38' SW to 5/8" iron pin

Station	Point Description	Witness Ties - Updated 11/29/05
62+21.43	RR Spike	7.62' NNE to 5/8" iron pin at edge of pavement 14.85' SSE to 5/8" iron pin at edge of pavement 14.71' WSW to 5/8" iron pin at edge of pavement
72+52.46	RR Spike	5.87' NNE to 5/8" iron pin at edge of pavement 15.99' S to 5/8" iron pin at edge of pavement 16.14' SW to 5/8" iron pin at edge of pavement 52.18' SE to duplex SW/side power pole
94+90.79	RR Spike	24.07' W to 5/8" iron pin at south edge of pavement 41.33' S to duplex in power pole
101+87.72	RR Spike	38.47' E to PK in west end corr. plastic pipe (P) 23.43' S to duplex E/side power pole 40.14' ESE to PK west end corr. plastic pipe (P)
113+67.87	RR Spike	15.23' E to 5/8" iron pin at edge of pavement 10.40' S to 5/8" iron pin (new) at edge of pavement 77.80' WNW to duplex N/side power pole
124+63.11	RR Spike	79.80' WNW to sawed "+" in catch basin (P) 55.45' SE to duplex NE/side power pole 25.05' SW to duplex E/side cable marker
137+03.20	RR Spike	26.05' ENE to sawed "+" east corner catch basin (P) 32.12' SSE to duplex SW/side power pole 20.36' WSW to PK east end CMP (P) 34.36' W to PK west end CMP (P) 20.64' S to sawed "+" north corner catch basin (P)

Station	Point Description	Witness Ties - Updated 11/29/05
151+55.99	RR Spike	41.33' NE to "+" north end conc. pipe (P) 60.56' SE to "+" south end conc. pipe 54.28' SW to duplex NW/side cable marker
156+79.03	RR Spike	68.49' NNW to "+" north end RCP (P) 34.98' E to 16d spike W/side cable marker 56.10' SE to "+" in center of headwall 18.63' SW to "+" in center of headwall
164+87.39	RR Spike	12.80' E to 5/8" iron pin at edge of pavement 19.05' SE to 5/8" iron pin at edge of pavement 16.65' W to 5/8" iron pin at edge of pavement
172+35.09	5/8" Iron Pin & PK' PK's 6' NW & NE	104.15' NW to duplex NE/side cable marker 22.27' NNE to 5/8" iron pin at edge of pavement (mark-mark measurement) 45.33' WSW to PK E/side clump of trees
177+72.93	RR Spike	14.08' N to 5/8" iron pin (new) at edge of pavement 10.01' SE to 5/8" iron pin at edge of pavement 10.18' SW to 5/8" iron pin (new) at edge of pavement

Witness Ties - Road Y

Station	Point Description	Witness Ties - Updated 11/28-29/05
177+72.93	RR Spike	14.08' N to 5/8" iron pin (new) at edge of pavement 10.01' SE to 5/8" iron pin at edge of pavement 10.18' SW to 5/8" iron pin (new) at edge of pavement
184+58.03	RR Spike	53.48' ENE to duplex W/side power pole 116.65' ESE to PK nail NW/side 12" tree
184+94.34	RR Spike	98.20' E to "+" in center conc. walk (P) 27.34' NNE to duplex W/side power pole 89.83' SE to PK nail NW/side 12" tree
185+29.46	RR Spike	44.47' NW to duplex E/side power pole 60.24' SE to PK nail NW/side 12" tree 64.98' ENE to "+" in center conc. walk (P)
189+15.97	RR Spike	76.80' SE to NW corner house foundation 71.91' SW to NE corner house foundation 71.18' NW to SE corner house foundation
194+65.92	RR Spike	47.92' SSE to near corner conc. foundation 62.45' WSW to "+" east end conc. walk 46.49' SE to duplex SW/side power pole

Station	Point Description	Witness Ties - Updated 11/28-29/05
199+90.40	RR Spike	19.75' SSW to "+" in conc. pipe (P) 46.69' NW to duplex S/side power pole 65.87' ENE to "+" in conc. slab
199+94.81	RR Spike 1" Below Surface	23.52' SSW to "+" in conc. pipe (P) 43.38' NW to duplex S/side power pole 64.41' ENE to "+" in conc. slab (barn)
203+95.25	RR Spike	23.82' NNE to duplex S/side power pole 59.46' WNW to duplex N/side power pole
207+07.69	PK Nail - No Head 1" Below Surface	63.50' N to SW corner porch foundation 60.70' NE to SW corner house foundation 76.16' SW to NE corner building foundation 104.20' SSE to NW corner house foundation (no field check) 39.21' NW to duplex SW/side telephone pole
214+51.61	RR Spike 2" Below Surface	39.00' NW to SW corner conc. drive 23.10' NE to sawed "+" SE corner conc. drive 33.97' E to "+" south end conc. curb 16.35' NE to duplex SE/side telephone pole 59.69' W to sawed "+" NE corner conc. drive
216+01.85	PK Nail on Surface	26.54' S to duplex N/side power pole 72.82' W to duplex N/side power pole 71.71' NNE to SW corner house foundation 28.47' NNW to duplex E/side telephone pole
217+31.93	PK Nail on Surface	91.28' N to SE corner brick house 20.92' NE to duplex S/side telephone pole 43.06' NW to sawed "+" SE corner conc. drive

Station	Point Description	Witness Ties - Updated 11/28-29/05
220+48.80	PK Nail 3" Below Surface	10.40' N to 5/8" iron pin at edge of pavement 23.82' WSW to sawed "+" in conc. drive (P)
221+68.84	RR Spike 2" Below Surface	31.03' S to "+" in conc. corner post 50.88' NW to duplex E/side cable post 23.18' N to "+" E/side 4" metal post (angled 0.8' to north) 17.33' NE to duplex W/side power pole
225+74.82	RR Spike	84.55' ESE to duplex S/side cable marker 58.47' NE to SW corner brick pump house 33.53' NW to sawed "+" in conc. drive
236+17.39	RR Spike	60.52' E to sawed "+" W/side conc. post 22.53' NE to duplex NW/side power pole 25.18' SSE to duplex W/side power pole 59.18' SW to NE corner house foundation (no field check)
242+96.83	RR Spike	52.00' NNE to duplex south root 24" tree 46.88' WNW to duplex S/side power pole 66.02' NW to duplex SE/side cable marker
249+97.85	PK Nail 1" Below Surface	13.39' WSW to iron pin at edge of pavement 14.49' NNW to iron pin at edge of pavement 108.42' E to "+" W/side conc. anchor post
256+65.81	PK Nail 1" Below Surface	30.83' NNW to duplex E/side cable marker 10.21' NNE to 5/8" iron pin at edge of pavement 20.11' W to 5/8" iron pin (new) at edge of pavement

Station	Point Description	Witness Ties - Updated 11/28-29/05
262+82.32	RR Spike 2" Below Surface	24.63' S to "+" south end of CMP 31.08' N to "+" north end of CMP 92.93' NE to SW corner house foundation (blocked by tree) 66.54' SE to "+" east end CIP (field drive)
277+58.26	RR Spike	15.57' NNE to "+" west end of headwall (P) 23.35' ENE to "+" east end of headwall (P) 43.15' SE to "+" east end of headwall (P)
282+73.31	RR Spike	35.15' NNE to duplex NE/side cable marker 21.67' NE to 5/8" iron pin at edge of pavement
286+17.63	RR Spike	10.16' SE to 5/8" iron pin at south edge of pavement 23.60' NNE to duplex W/side of power pole 11.96' SW to 5/8" iron pin at south edge of pavement
290+46.56	RR Spike	44.00' SW to sawed "+" NW corner conc. drive 51.52' NNW to SW corner house foundation 51.90' NE to SE corner house foundation 25.73' SSE to duplex (new) E/side telephone pole
297+06.82	Iron Pin 1" Below Surface	32.60' SE to duplex SW/side telephone pole 59.45' NNE to SW corner brick porch 29.69' NW to duplex SW/side power pole 24.55' SE to sawed notch in NW corner pump house
304+61.79	Nail & Shiner Surface of SR 108	82.05' WNW to duplex S/side power pole 49.56' NW to duplex SW/side power pole 34.19' NE to "+" north end conc. pipe (P) 45.01' ENE to duplex S/side wood post 33.40' SE to "+" south end conc. pipe (P)

Station	Point Description	Witness Ties - Updated 11/28-29/05
317+85.04	RR Spike	44.88' NW to "+" in conc. curb 28.11' N to sawed notch SW corner of block pillar 32.82' S to duplex E/side power pole 76.71' SW to near face of well casing flange
319+86.60	RR Spike	27.96' S to duplex E/side cable marker post 25.46' N to sawed notch SE corner of block pillar 86.04' ESE to duplex SW/side power pole
326+52.21	I.P. 5.5' N of E/P Set PK 10' SE&SW	55.57' E to duplex S/side cable marker post 48.30' SE to duplex N/side power pole (P) 51.65' SW to duplex SE/side power pole (P) 44.63' WNW to duplex S/side brace pole 77.03' SE to "+" NW corner catch basin (P) (buried)
341+53.17	RR Spike	85.21' SE to duplex N/side power pole 11.70' SW to 5/8" iron pin at edge of pavement 37.34' NW to duplex S/side cable marker 10.94' NE to 5/8" iron pin at edge of pavement
353+29.52	Small RR Spike	71.19' WNW to duplex NE/side power pole 8.53' NNE to 5/8" iron pin at edge of pavement 18.12' SE to 5/8" iron pin at edge of pavement
362+98.59	RR Spike	28.56' SW to duplex NW/side power pole 86.75' SSW to duplex E/side power pole 20.20' NE to duplex SE/side cable marker